

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765 Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

MULTITRANS ATF

PRODUCT DESCRIPTION

Hi-Tec MULTITRANS ATF is a premium synthetic automatic transmission fluid specifically designed for use in North American, European and Asian vehicles. **Hi-Tec MULTITRANS ATF** has exceptional oxidative resistance, anti-wear performance and frictional stability. It provides excellent antirust properties and sludge and varnish control. Its multivehicle applicability allows reduction of inventory of transmission fluids.

Hi-Tec MULTITRANS ATF is formally approved to Ford Mercon[®] V, Allison C-4 and JASO 1-A requirements. It is suitable for use in equipment requiring GM Dexron[®] IIIH, Ford Mercon and Ford / BTR 4 speed 85 and 95 LE fluids (new approvals are no longer possible for these specifications).

BENEFITS

Hi-Tec MULTITRANS ATF allows for rapid oil flow to all critical transmission components (i.e. torque converters, friction plates, planetary wheels and brake bands). It provides more responsive and comfortable gear shifts and minimizes 'shift shock' when gear shifts occur at low temperature. Reduced torque loss increases efficiency leading to fuel savings and lower emissions.

Hi-Tec MULTITRANS ATF promotes **s**moother gear shifts at all ambient temperatures and load conditions. Its consistent frictional properties improve driver comfort and very long anti shudder durability for comfortable gear changes without noise, vibration or harshness. **Hi-Tec MULTITRANS ATF** avoids foaming tendencies in transmissions so that full-bodied lubricant is maintained to all surfaces requiring lubrication.

Viscosity changes with usage remain minimal with **Hi-Tec MULTITRANS ATF** helping prevent deposits and oil thickening. This extends transmission life. Excellent transmission cleanliness under high temperature and high load conditions permits extended oil drain intervals and decreased servicing.

SPECIFICATIONS

Hi-Tec MULTITRANS ATF can be formally approved for: Mercon V JASO 1-A Allison C-4

Hi-Tec MULTITRANS ATF meets the following demanding performance requirements: GM Dexron III H Ford Mercon, BTR 85, 95LE

Hi-Tec MULTITRANS ATF will provide suitable performance in numerous passenger cars applications including:

AE, Aisin Warner, Audi, BMW, Chrysler, Daimler, Ford Mercon, GM Dexron, Honda, Hyundai, JASO, JATCO, JWS, Kia, Mazda, Mercedes Benz, Mitsubishi, Nissan, Saab, Subaru, Toyota, Volvo, VW and ZF; as well as commercial applications including Allison, MAN, Voith and MB (see Multitrans ATF Part B for a full list).



AUSTRALIAN FAMILY OWNED SINCE 1989



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765 Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au



* Note: MULTITRANS ATF is not suitable for use with Continuously Variable Transmissions, Dual Clutch Transmissions or Ford Type F applications.

Always consult your vehicle owner's manual for the manufacturer's lubricant recommendations.

<u>TYPICAL PROPERTIES</u>				
ASTM Method	Results			
Visual	Red			
	0.851			
	34.32			
	7.21			
	12,000			
ASTM D97	-48			
ASTM D92	204			
ASTM D892	Pass			
ASTM D130, 665A	Pass			
DIN 513554	>12			
	Visual ASTM D97 ASTM D92 ASTM D892 ASTM D130, 665A			

Available in: 200 Litres, 60 Litres, 20 Litres, 5 Litres, 1 Litre

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at <u>www.hi-tecoils.com.au</u>. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code:		HI3-2684	

Effective:January 2017Expires:January 2019

TN711061/1

