



## 22-Safety Data Sheet

### Aerosol Curtain Track Lube

#### COMPANY AND PRODUCT IDENTIFICATION

<b>Company Name</b>	Wolfchester Australia Pty Ltd	Distributor
<b>ABN</b>	25 120 690 682	Autoserv New Zealand Ltd
<b>Address</b>	4/122 Beresford Road, Lilydale VIC	2/38 Trugood Drive
<b>Emergency Tel:</b>	(+613) 9737 2800	East Tamaki, Auckland
		Phone: +64 9 272 1940
<b>Tel / Fax:</b>	(+613) 9737 2800	Emergency 0800 2436 2255/
<b>Email:</b>	sales@wolfchester.com.au	0800 764 766
		warehouse@autoserv.co.nz
<b>Product Name</b>	Wolfchester Curtain Track Lubricant	
<b>Other Names</b>	300g Not relevant	
<b>Manufacturers Code</b>	TAUS320CTL	
<b>Recommended use</b>	Lubricant for curtain tracks	

#### Poisons Information Centre

<b>AUSTRALIA</b>	13 11 26
<b>NEW ZEALAND</b>	0800 764 766 or 0800 POISON

#### HAZARD(S) IDENTIFICATION

<b>Hazard Classification</b>	<p>This product is classified as hazardous under Australian WHS Regulations. This product is classified as a Dangerous Good by the Australian Dangerous Goods Code.</p> <p>Flammable Aerosols, Cat 1 Skin Corrosion/Irritation, Cat 2 Reproductive Toxicity, Cat 2 Aspiration Toxicity, Cat 1 Specific Target Organ Toxicity (Single Exposure), Cat 3 Specific Target Organ Toxicity (Repeated Exposure), Cat2 Aquatic Toxicity, Chronic Cat 2</p>
<b>Hazard Statement(s)</b>	<p>Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.</p> <p>H222 Extremely flammable aerosol.</p> <p>H305 May be harmful if swallowed and enters airways</p> <p>H315 Causes skin irritation</p> <p>H336 May cause drowsiness or dizziness</p> <p>H361 Suspected of damaging fertility or the unborn child</p> <p>H373 May cause damage to organs through prolonged or repeated exposure</p> <p>H411 Toxic to aquatic life with long lasting effects</p>
<b>Signal</b>	Danger

## 22-Safety Data Sheet

### Aerosol Curtain Track Lube

#### Hazard Symbol



#### Precautionary Statement(s)

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat/sparks/open flames/hot surfaces - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P262 Do not get in eyes, on skin, or on clothing.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302 IF ON SKIN: remove contaminated clothing and wash thoroughly.  
P301 + P310 IF SWALLOWED: immediately call a POISON CENTER or doctor/physician.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P312 Call a POISON CENTER/ doctor if you feel unwell.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P273 Avoid release to the environment.

For further health and safety information please refer to the full SDS.

Note: This product should not be used in any purpose or manner contrary to recommended use unless authorised.

### COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Proportion
Naphtha (petroleum), hydrotreated light	64742-49-0	10-30%
n-Hexane	110-54-3	<10%
Hydrocarbon propellant		10-30%
- Propane	74-98-6	
- Butane	106-97-8	
Other ingredients		to 100%

## 22-Safety Data Sheet

### Aerosol Curtain Track Lube

#### FIRST AID MEASURES

For advice, contact a Poisons Information Centre 131126 or a doctor. Ensure medical personnel are aware of the identity and nature (hydrocarbon propelled aerosol) involved.

**Inhalation:** Remove victim to fresh air to prevent further exposure. Propane is an asphyxiant. Fumes may cause drowsiness or dizziness. If breathing difficulties are experienced, seek immediate medical care. Do not use direct mouth to mouth method of resuscitation, use alternative respiratory method.

**Skin Contact:** Remove contaminated clothing and shoes and wash well skin with warm soapy water. If irritation persists, contact a doctor.

**Eye Contact:** Flush out immediately with running water for at least 15 minutes. If symptoms persist, seek medical attention.

**Ingestion:** Due to high volatility of product, this is not likely to occur. If sprayed in mouth, rinse mouth with plenty of water. If swallowed, do NOT induce vomiting. Seek medical attention.

#### FIRE FIGHTING MEASURES

Beware – heat greater than 50 C / 122 °F may cause these extremely flammable, pressurised dispensers to rupture, and violently rocket in various directions. These rockets will release flammable and potentially toxic gases, which will increase the risk of fire spreading. In extinguishing any fire beware of any residual unburnt gas that could reignite.

**Suitable Extinguishing Media/ Hazards** Small fire: Use water spray/fog/foam, dry chemical or carbon dioxide (CO<sub>2</sub>).  
Large fire: Use water spray/fog/foam.

Aerosols may rupture and rocket (become projectiles) when exposed to excessive heat. Released gases can form extremely flammable, invisible, odourless explosive mixtures with air. Released gases can be heavier than air and travel to source of ignition causing flashback. Hazardous concentrations can accumulate in a confined space (pits, low laying areas). Fire can produce irritating, poisonous and corrosive gases. High concentration of gas could cause dizziness or asphyxiation without warning.

**Precautions / PPE** For large quantities, consider initial evacuation for at least 100m in all directions.  
Fight fire from protected position or use unmanned hose holders or monitor nozzles.  
Use spark-proof tools and explosion-proof equipment.  
Wear SCBA and protective gloves. Structural firefighter's uniform provides limited protection. If large amounts are involved, wear SCBA and chemical splash suit.  
If impossible to safely extinguish fire, protect surroundings, withdraw from area and allow fire to burn.  
If safe to do so, move undamaged aerosols from fire area but do not approach hot aerosols.  
Cool aerosols with water before handling.

**Hazchem Code (for Placarding and transport)** 2YE  
Class 2 flammable gas

## 22-Safety Data Sheet

### Aerosol Curtain Track Lube

only)

#### ACCIDENTAL RELEASE MEASURES

##### **Personal Precautions, PPE and Emergency Procedures**

Spill is flammable (until LPG dissipates). Eliminate all sources of ignition including static discharge. Wear protective gloves and safety glasses to prevent contamination of skin and eyes.

Minor spills: Keep area well ventilated and wipe up.

Major spills:

Isolate spill or leak area for at least 8 m in all directions. Eliminate all sources of ignition within at least 15 m.

Keep upwind and to higher ground (propellant gas is heavier than air and will seek low points, pay special attention to drains and pits- these will likely be explosive environments).

Major fire:

Consider initial evacuation for at least 100 m in all directions

##### **Environmental Precautions Containment / Clean up Procedures**

Notify police and fire brigade of the location, material, UN Number, quantity and emergency contact as well as condition and damage observed.

Keep leaking containers away from drains, surface and ground water. Ensure leakage does not enter streams, sewers or drinking water supply.

Eliminate all ignition sources, including static within at least 15 m. All equipment used when handling the product must be earthed.

If water is available, spray leaking containers to reduce ignition hazard and disperse gas. Isolate area until gas has dispersed. Ventilate area. Avoid release to the environment. Do not empty into drains or natural waterways. Absorb spill with inert absorbent material (e.g. dry sand or earth) for disposal using an approved method or following local regulations.

#### HANDLING AND STORAGE

##### **Precautions for Safe Handling**

Ensure spray nozzle is always directed away from user. Do not pierce or burn can after use. Extremely flammable- Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Do not breathe concentrated, vapour, mist or spray. Local exhaust ventilation may be necessary to minimise excessive vapour concentration (as long as they do not introduce risk of ignition), if levels are likely to be high or in a confined space.

##### **Conditions for Safe Storage**

Keep out of reach of children. Store in a well-ventilated area, away from damp or corrosive conditions. Protect from sunlight and do not expose to temperatures exceeding 50 °C / 122 °F. Store in accordance with Dangerous Goods Regulations and transport in accordance with the ADG Code for Dangerous Goods Class 2.1

#### EXPOSURE CONTROLS / PERSONAL PROTECTION

##### **National**

There is no established TLV (Threshold Limit Value) for this product.

## 22-Safety Data Sheet

### Aerosol Curtain Track Lube

<b>Exposure Standards</b>	Avoid exposure – obtain special instructions before use. Butane - TWA (Time-Weighted Average) is 800ppm / 1900mg/m <sup>3</sup> Propane is an asphyxiant
<b>Biological Limit Values</b>	Not available.
<b>Engineering Controls</b>	No smoking. No flames or sources of ignition. Local exhaust ventilation may be necessary to minimise excessive vapour concentration, if levels are likely to be high or in a confined space.
<b>Personal Protective Equipment (PPE)</b>	Personal Protective Equipment is not required under normal conditions of use. When handling bulk quantities, wear protective gloves and safety glasses. Do not exceed exposure limits.

### PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Aerosol, Clear spray
<b>Odour</b>	Solvent like
<b>pH</b>	Not applicable
<b>Vapour Pressure</b>	Not available
<b>Vapour Density</b>	Not available
<b>Boiling point (propellant)</b>	-42 to 0°C
<b>Solubility in Water</b>	Immiscible
<b>Specific Gravity (propellant)</b>	0.58 approx
<b>Flash Point (propellant)</b>	-104 to -60°C
<b>Flammable limits (propellant)</b>	1.5% to 9.6% in air (v/v)
<b>Ignition Temperature (propellant)</b>	494°C to 600°C

### STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under normal ambient conditions of storage and use. Avoid heat/ignition sources. Aerosol cans may explode/burst violently when subject to extremes of heat or pressure and may become projectiles.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid static charge and discharge with high concentrations and in confined space. Avoid damp or corrosive conditions.
<b>Incompatible Materials / Hazardous Reactions</b>	Can react violently with oxidising agents, mineral acids, phosphorous, chlorine.
<b>Hazardous Decomposition Products</b>	Products may include carbon monoxide, carbon dioxide, organic complexes

### TOXICOLOGICAL INFORMATION

<b>Potential adverse health</b>	Vapours may cause light-headedness, drowsiness and dizziness.
---------------------------------	---

## 22-Safety Data Sheet

### Aerosol Curtain Track Lube

**effects and symptoms  
associated with exposure  
to the material**

**Ingestion:** Unlikely due to high volatility of product.

**Eyes:** Liquid will cause severe irritation. Vapour may cause irritation.

**Skin:** May cause cold burn. Irritating to skin. May result in dryness and cracking.

**Inhalation:** Produces hallucinations and narcotic effect. Ingestion of large amounts will result in drowsiness, fatigue, loss of appetite, paresthesia in distal extremities (tingling in hands and feet). Possibility of muscle weakness, cold pulsation in extremities (hands and feet), blurred vision, headache, and nausea. Vomiting may cause this product to be aspirated to the lungs resulting in chemical pneumonitis or pulmonary oedema. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. May cause light-headedness, dizziness and drowsiness. Excessive exposure may cause unconsciousness or even death, due to asphyxiation.

### ECOLOGICAL INFORMATION

The information provided is based on data available for the material and the components of the material.

**Ecotoxicity / Persistence  
/ Degradability /  
Mobility**

Propellant will vaporise rapidly when released to atmosphere.  
Propellant consists of hydrocarbons that photo chemically decompose under atmospheric conditions.

### DISPOSAL CONSIDERATIONS

**Consumer Instructions  
Bulk quantities**

Recycle empty can.  
Empty containers might contain residue and can be dangerous. Do not pierce or burn, even when empty.  
Dispose of according to Local, State and National regulations.

### TRANSPORT INFORMATION

Transport in accordance with the requirements of ADG Code.

<b>UN Number</b>	1950
<b>Proper Shipping Name (ADG 7, IMDG)</b>	AEROSOLS
<b>Proper Shipping name (IATA)</b>	AEROSOLS, FLAMMABLE
<b>Emergency Procedure Guide</b>	2D1
<b>Class and subsidiary risk(s)</b>	2.1
<b>Packaging Group</b>	None allocated
<b>Hazchem Code</b>	2YE
<b>Special Precautions for Users</b>	Keep out of reach of children. Spray in well-ventilated area.

## 22-Safety Data Sheet

### Aerosol Curtain Track Lube

Keep away from sources of ignition – No smoking.  
Extremely flammable - Do not spray on a naked flame or any incandescent material.  
Do not breathe vapour/mist/spray.  
Wear protective gloves, eye protection and suitable respirator when mixing or using.

### REGULATORY INFORMATION

<b>Poisons Schedule</b>	N/A
<b>Additional information</b>	Not applicable