Wynn's Engine Flush

Autoserv NZ Ltd

Chemwatch Hazard Alert Code: 2

Chemwatch: **4852-53** Version No: **3.1** Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017 Issue Date: 01/11/2019 Print Date: 18/07/2022 S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Wynn's Engine Flush
Chemical Name	Not Applicable
Synonyms	65901 325 ml
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

	Relevant identified uses	Cleaning fluid for vehicle engines.
--	--------------------------	-------------------------------------

Details of the supplier of the safety data sheet

Registered company name	Autoserv NZ Ltd	
Address	Unit 2/38 Trugood Drv, East Tamaki 2013 New Zealand	
Telephone	0800 438 996	
Fax	Fax Not Available	
Website Not Available		
Email warehouse@autoserv.co.nz		

Emergency telephone number

Association / Organisation	Autoserv NZ Ltd	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	+800 2436 2255 (All Hours)	+64 800 700 112
Other emergency telephone numbers	0800 764 766	+61 3 9573 3188

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Acute Toxicity (Oral) Category 5, Aspiration Hazard Category 1, Acute Toxicity (Dermal) Category 5, Skin Corrosion/Irritation Category 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Carcinogenicity Category 2, Flammable Liquids Category 4	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by Chemwatch using GHS/HSNO criteria 3.1D, 6.1E (aspiration), 6.1E (dermal), 6.1E (oral), 6.3B, 6.7B, 6.9B (narcotic effects)		

Label elements

Hazard pictogram(s)



Signal word Danger

Hazard statement(s)

H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H316	Causes mild skin irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H227	Combustible liquid.

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and protective clothing.

Precautionary statement(s) Response

P301+P310	P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.	
P331 Do NOT induce vomiting.		
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.		
P302+P312	IF ON SKIN: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.	

Precautionary statement(s) Storage

P405 Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64741-97-5.	30-60	naphthenic distillate, light, solvent-refined (severe)
68476-34-6	30-60	middle distillate
Not Available	<10	other non-hazardous ingredients
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Page **3** of **10** Wynn's Engine Flush

Continued...

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	---

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx)

sulfur oxides (SOx)

other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Slippery when spilt. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	 Slippery when spilt. Remove all ignition sources. Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid storage with oxidisers

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	naphthenic distillate, light, solvent-refined (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	(om)-Sampled by a method that does not collect vapour.

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
naphthenic distillate, light, solvent-refined (severe)	1,100 mg/m3	1,800 mg/m3	40,000 mg/m3
middle distillate	300 mg/m3	3,300 mg/m3	20,000 mg/m3

Wynn's Engine Flush

Ingredient	Original IDLH	Revised IDLH
naphthenic distillate, light, solvent-refined (severe)	2,500 mg/m3	Not Available
middle distillate	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	 Safety glasses with side shields; or as required, Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	 Overalls. Eyewash unit.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear thin amber liquid with mild petroleum odour; does not mix with water.			
Physical state	Liquid	Relative density (Water = 1)	0.878	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available	
Melting point / freezing point (°C)	-32	Viscosity (cSt)	5.0	
Initial boiling point and boiling range (°C)	163-371	Molecular weight (g/mol)	Not Applicable	
Flash point (°C)	79 (PMCC)	Taste	Not Available	
Evaporation rate	Not Available	Explosive properties	Not Available	
Flammability	Combustible.	Oxidising properties	Not Available	
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available	
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available	
Vapour pressure (kPa)	Negligible	Gas group	Not Available	
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Applicable	

VOC g/L

Not Available

Vapour density (Air = 1) >1

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of vapour is more likely at higher than normal temperatures.
Ingestion	Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.
Skin Contact	The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS] Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.

Wynn's Engine Flush	TOXICITY	IRRITATION
	Not Available	Not Available
	ΤΟΧΙΟΙΤΥ	IRRITATION
aphthenic distillate, light,	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
solvent-refined (severe)	Inhalation(Rat) LC50; 2.18 mg/l4h ^[2]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; >5000 mg/kg ^[2]	
	TOXICITY	IRRITATION
	TOXICITY Dermal (rabbit) LD50: >1800 mg/kg ^[1]	IRRITATION Eye: no adverse effect observed (not irritating) ^[1]
middle distillate		

	Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins.
	The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the
NAPHTHENIC DISTILLATE,	hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the
LIGHT, SOLVENT-REFINED	lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell.
(SEVERE)	The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives;
	The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has
	undergone, since:
	The adverse effects of these materials are associated with undesirable components, and
	The levels of the undesirable components are inversely related to the degree of processing;
	Distillate base oils receiving the same degree or extent of processing will have similar toxicities;

Chemwatch: 4852-53	
Part Number:	
Version No: 3.1	

Page 7 of 10
Wynn's Engine Flush

	 The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size. Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. For highly and severely refined distillate base oils: In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity to humans. 		
NAPHTHENIC DISTILLATE, LIGHT, SOLVENT-REFINED (SEVERE) & MIDDLE DISTILLATE	No significant acute toxicological data identified in literature search.		
Acute Toxicity	~	Carcinogenicity	✓
Skin Irritation/Corrosion	*	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	*
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	~

SECTION 12 Ecological information

Toxicity

Wynn's Engine Flush	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
naphthenic distillate, light, solvent-refined (severe)	NOEC(ECx)	504h	Crustacea	>1mg/l	1
Solvent-renned (Severe)	EC50	48h	Crustacea	>1000mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
middle distillate	EC50(ECx)	288h	Algae or other aquatic pla	nts 20mg/l	1
Legend:		, ,	ECHA Registered Substances - Ecotox ata 5. ECETOC Aquatic Hazard Assessr	a 1	

DO NOT discharge into sewer or waterways.

Persistence and degradability		
Ingredient	Persistence: Water/Soil Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients

Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Ingredient	Mobility	
	No Data available for all ingredients	

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
naphthenic distillate, light, solvent-refined (severe)	Not Available
middle distillate	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
naphthenic distillate, light, solvent-refined (severe)	Not Available
middle distillate	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002513	Additives, Process Chemicals and Raw Materials (Combustible, Toxic [6.7]) Group Standard 2006	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

naphthenic distillate, light, solvent-refined (severe) is found on the following regulatory lists

Chemwatch: 4852-53	Page 9	of 10	Issue Date: 01/11/2019
Part Number:	Wynn's Eng	uine Elush	Print Date: 18/07/2022
Version No: 3.1			
Chemical Footprint Project - Chemicals of High	n Concern List	New Zealand Hazardous Substances and	d New Organisms (HSNO) Act -
International Agency for Research on Cancer (IARC) - Agents Classified by		Classification of Chemicals	
the IARC Monographs		New Zealand Inventory of Chemicals (NZ	ZIoC)
New Zealand Approved Hazardous Substances with controls		New Zealand Workplace Exposure Stand	dards (WES)
middle distillate is found on the following r	egulatory lists		

New Zealand Inventory of Chemicals (NZIoC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities	
Not Applicable	Not Applicable	

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities	
Not Applicable	Not Applicable	

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
3.1C or 3.1D				10 L

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (naphthenic distillate, light, solvent-refined (severe); middle distillate)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	No (naphthenic distillate, light, solvent-refined (severe); middle distillate)		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	No (naphthenic distillate, light, solvent-refined (severe))		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

 Chemwatch: 4852-53
 Page 10 of 10
 Issue Date: 01/11/2019

 Part Number:
 Wynn's Engine Flush
 Print Date: 18/07/2022

 Version No: 3.1
 Print Date: 18/07/2022

Revision Date	01/11/2019
Initial Date	21/12/2012

SDS Version Summary

Version	Date of Update	Sections Updated
2.1	21/12/2012	Acute Health (swallowed), Advice to Doctor, Appearance, Chronic Health, Classification, Exposure Standard, Fire Fighter (fire/explosion hazard), First Aid (swallowed), Handling Procedure, Ingredients, Personal Protection (other), Personal Protection (eye), Physical Properties, Supplier Information, Use
3.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.